

※日本冷凍空調工業会標準規格JRA4048：2006に定める条件〔地区：東京、建物用途：戸建て店舗〕。APF区分についての詳細はP.183の表を参照ください。

FIVE STAR ZEAS シリーズ

形式	機種名	APF (区分)	冷暖平均COP
天井埋込カセット形 S-ラウンドフロー<センシング>タイプ			
標準ペア	SSRC40BY(N)V	6.7 (ab)	5.06
	SSRC40BY(N)T	6.7 (ab)	5.06
	SSRC45BY(N)V	6.7 (ab)	4.84
	SSRC45BY(N)T	6.7 (ab)	4.84
	SSRC50BY(N)V	6.6 (ab)	4.68
	SSRC50BY(N)T	6.6 (ab)	4.68
	SSRC56BY(N)V	6.4 (ab)	4.42
	SSRC56BY(N)T	6.4 (ab)	4.42
	SSRC63BY(N)V	6.3 (ab)	4.44
	SSRC63BY(N)T	6.3 (ab)	4.44
	SSRC80BY(N)V	6.3 (ab)	4.72
	SSRC80BY(N)T	6.4 (ab)	4.77
	SSRC112BY(N)	6.4 (ac)	4.72
	SSRC140BY(N)	6.0 (ac)	4.16
ツイン同時	SSRC160BY(N)	5.8 (ac)	3.92
	SSRC80BY(N)V D	6.3 (ab)	4.78
	SSRC80BY(N)T D	6.3 (ab)	4.78
	SSRC112BY(N) D	6.4 (ac)	4.46
	SSRC140BY(N) D	6.1 (ac)	4.31
	SSRC160BY(N) D	5.9 (ac)	4.11
トリプル同時	SSRC160BY(N) M	6.0 (ac)	4.11
天井吊形 スタイリッシュフロー			
標準ペア	SSRHU40BYV	5.7 (af)	4.35
	SSRHU40BYT	5.7 (af)	4.35
	SSRHU50BYV	5.5 (af)	3.88
	SSRHU50BYT	5.5 (af)	3.88
	SSRHU63BYV	5.5 (af)	3.61
	SSRHU63BYT	5.5 (af)	3.61
	SSRHU80BYV	5.0 (af)	3.40
	SSRHU80BYT	5.0 (af)	3.40
ツイン同時	SSRHU80BYV D	5.1 (af)	3.69
	SSRHU80BYT D	5.1 (af)	3.69
	SSRHU112BYD	5.5 (ag)	3.84
	SSRHU140BYD	5.1 (ag)	3.59
	SSRHU160BYD	5.0 (ag)	3.19
トリプル同時	SSRHU160BYM	5.0 (ag)	3.49
天井埋込カセット形 エコ・ダブルフロー<センシング>タイプ			
標準ペア	SSRG40BY(N)V	5.6 (af)	4.53
	SSRG40BY(N)T	5.6 (af)	4.53
	SSRG45BY(N)V	5.6 (af)	4.11
	SSRG45BY(N)T	5.6 (af)	4.11
	SSRG50BY(N)V	5.4 (af)	3.93
	SSRG50BY(N)T	5.4 (af)	3.93
	SSRG56BY(N)V	5.2 (af)	3.53
	SSRG56BY(N)T	5.2 (af)	3.53
	SSRG63BY(N)V	5.2 (af)	3.67
	SSRG63BY(N)T	5.2 (af)	3.67
	SSRG80BY(N)V	5.0 (af)	3.69
	SSRG80BY(N)T	5.0 (af)	3.69
	SSRG112BY(N)	5.5 (ag)	4.00
	SSRG140BY(N)	5.1 (ag)	3.38
	SSRG160BY(N)	5.0 (ag)	3.06
ツイン同時	SSRG80BY(N)V D	5.2 (af)	3.98
	SSRG80BY(N)T D	5.2 (af)	3.98
	SSRG112BY(N) D	5.5 (ag)	3.88
	SSRG140BY(N) D	5.1 (ag)	3.43
	SSRG160BY(N) D	5.0 (ag)	3.29
トリプル同時	SSRG160BY(N) M	5.2 (ag)	3.40
天吊自在形 ワンダ風流<センシング>タイプ			
標準ペア	SSRU40BY(N)V	5.6 (af)	4.61
	SSRU40BY(N)T	5.6 (af)	4.61
	SSRU50BY(N)V	5.4 (af)	4.04
	SSRU50BY(N)T	5.4 (af)	4.04
	SSRU63BY(N)V	5.2 (af)	3.74
	SSRU63BY(N)T	5.2 (af)	3.74
	SSRU80BY(N)V	5.3 (af)	3.89
	SSRU80BY(N)T	5.3 (af)	3.89
	SSRU112BY(N)	5.5 (ag)	4.04
	SSRU140BY(N)	5.1 (ag)	3.35
ツイン同時	SSRU80BY(N)V D	5.5 (af)	4.10
	SSRU80BY(N)T D	5.5 (af)	4.10
	SSRU112BY(N) D	5.6 (ag)	4.20
	SSRU140BY(N) D	5.6 (ag)	4.00
	SSRU160BY(N) D	5.4 (ag)	3.66
トリプル同時	SSRU160BY(N) M	5.5 (ag)	3.85

形式	機種名	APF (区分)	冷暖平均COP
天井埋込カセット形 シングルフロー<センシング>タイプ			
標準ペア	SSRK40BY(N)V	5.6 (af)	4.12
	SSRK40BY(N)T	5.6 (af)	4.12
	SSRK45BY(N)V	5.3 (af)	3.90
	SSRK45BY(N)T	5.3 (af)	3.90
	SSRK50BY(N)V	5.2 (af)	3.80
	SSRK50BY(N)T	5.2 (af)	3.80
	SSRK56BY(N)V	5.2 (af)	3.62
	SSRK56BY(N)T	5.2 (af)	3.62
	SSRK63BY(N)V	5.3 (af)	3.62
	SSRK63BY(N)T	5.3 (af)	3.62
	SSRK80BY(N)V	5.0 (af)	3.49
	SSRK80BY(N)T	5.0 (af)	3.49
ツイン同時	SSRK80BY(N)V D	5.1 (af)	3.84
	SSRK80BY(N)T D	5.1 (af)	3.84
	SSRK112BY(N) D	5.4 (ag)	3.84
	SSRK140BY(N) D	5.1 (ag)	3.59
	SSRK160BY(N) D	5.0 (ag)	3.19
トリプル同時	SSRK160BY(N) M	5.0 (ag)	3.49
天井吊形<センシング>タイプ			
標準ペア	SSRH40BY(N)V	5.6 (af)	4.34
	SSRH40BY(N)T	5.6 (af)	4.34
	SSRH45BY(N)V	5.4 (af)	4.16
	SSRH45BY(N)T	5.4 (af)	4.16
	SSRH50BY(N)V	5.4 (af)	3.84
	SSRH50BY(N)T	5.4 (af)	3.84
	SSRH56BY(N)V	5.3 (af)	3.83
	SSRH56BY(N)T	5.3 (af)	3.83
	SSRH63BY(N)V	5.3 (af)	3.70
	SSRH63BY(N)T	5.3 (af)	3.70
	SSRH80BY(N)V	5.3 (af)	3.56
	SSRH80BY(N)T	5.3 (af)	3.64
	SSRH112BY(N)	5.6 (ag)	4.08
	SSRH140BY(N)	5.3 (ag)	3.38
	SSRH160BY(N)	5.1 (ag)	3.07
ツイン同時	SSRH80BY(N)V D	5.2 (af)	3.94
	SSRH80BY(N)T D	5.2 (af)	3.94
	SSRH112BY(N) D	5.5 (ag)	3.81
	SSRH140BY(N) D	5.4 (ag)	3.81
	SSRH160BY(N) D	5.2 (ag)	3.56
トリプル同時	SSRH160BY(N) M	5.2 (ag)	3.54
壁掛形			
標準ペア	SSRA40BY(N)V	5.6 (af)	4.32
	SSRA40BY(N)T	5.6 (af)	4.32
	SSRA45BY(N)V	5.4 (af)	4.02
	SSRA45BY(N)T	5.4 (af)	4.02
	SSRA50BY(N)V	5.2 (af)	3.91
	SSRA50BY(N)T	5.2 (af)	3.91
	SSRA56BY(N)V	5.2 (af)	3.73
	SSRA56BY(N)T	5.2 (af)	3.73
	SSRA63BY(N)V	5.3 (af)	3.74
	SSRA63BY(N)T	5.3 (af)	3.74
	SSRA80BY(N)V	5.1 (af)	3.61
	SSRA80BY(N)T	5.1 (af)	3.61
	SSRA112BY(N)	5.2 (ag)	3.45
ツイン同時	SSRA80BY(N)V D	5.4 (af)	4.00
	SSRA80BY(N)T D	5.4 (af)	4.00
	SSRA112BY(N) D	5.4 (ag)	3.67
	SSRA140BY(N) D	5.1 (ag)	3.59
	SSRA160BY(N) D	5.0 (ag)	3.22
トリプル同時	SSRA160BY(N) M	5.0 (ag)	3.32
天井埋込カセット形 ビルトインHiタイプ			
標準ペア	SSRB40BYV	5.6 (af)	3.84
	SSRB40BYT	5.6 (af)	3.84
	SSRB45BYV	5.4 (af)	3.56
	SSRB45BYT	5.4 (af)	3.56
	SSRB50BYV	5.4 (af)	3.51
	SSRB50BYT	5.4 (af)	3.51
	SSRB56BYV	5.3 (af)	3.50
	SSRB56BYT	5.3 (af)	3.50
	SSRB63BYV	5.3 (af)	3.53
	SSRB63BYT	5.3 (af)	3.53
	SSRB80BYV	5.2 (af)	3.81
	SSRB80BYT	5.2 (af)	3.81
	SSRB112BY	5.6 (ag)	4.31
	SSRB140BY	5.2 (ag)	3.94
	SSRB160BY	4.9 (ag)	3.57

形式	機種名	APF (区分)	冷暖平均COP
ツイン同時	SSRB80BYVD	5.2 (af)	3.84
	SSRB80BYTD	5.2 (af)	3.84
	SSRB112BYD	5.4 (ag)	4.25
	SSRB140BYD	5.2 (ag)	3.96
	SSRB160BYD	5.1 (ag)	3.58
トリプル同時	SSRB160BYM	5.1 (ag)	3.59
天井埋込ダクト形 標準タイプ			
標準ペア	SSRMM50BYV	5.3 (af)	3.56
	SSRMM50BYT	5.3 (af)	3.56
	SSRMM63BYV	5.3 (af)	3.78
	SSRMM63BYT	5.3 (af)	3.78
	SSRMM80BYV	5.0 (af)	3.96
	SSRMM80BYT	5.0 (af)	3.96
	SSRMM112BY	5.4 (ag)	4.27
	SSRMM140BY	5.2 (ag)	3.88
	SSRMM160BY	4.9 (ag)	3.52
天井埋込ダクト形 高静圧タイプ			
標準ペア	SSRM50BYV	4.8 (af)	3.49
	SSRM50BYT	4.8 (af)	3.49
	SSRM63BYV	4.8 (af)	3.75
	SSRM63BYT	4.8 (af)	3.75
	SSRM80BYV	4.6 (af)	3.51
	SSRM80BYT	4.6 (af)	3.51
	SSRM112BY	5.2 (ag)	3.93
	SSRM140BY	5.0 (ag)	3.33
	SSRM160BY	4.8 (ag)	3.39
天井埋込カセット形 マルチフロータイプ<ショーカセ>			
標準ペア	SSRN40BY(N)V	4.6 (ab)	3.89
	SSRN40BY(N)T	4.6 (ab)	3.89
	SSRN45BY(N)V	4.6 (ab)	3.68
	SSRN45BY(N)T	4.6 (ab)	3.68
	SSRN50BY(N)V	4.6 (ab)	3.46
	SSRN50BY(N)T	4.6 (ab)	3.46
	SSRN56BY(N)V	4.6 (ab)	3.46
	SSRN56BY(N)T	4.6 (ab)	3.46
	SSRN63BY(N)V	4.5 (ab)	3.18
	SSRN63BY(N)T	4.5 (ab)	3.18
ツイン同時	SSRN80BY(N)V D	5.2 (ab)	3.86
	SSRN80BY(N)T D	5.2 (ab)	3.86
	SSRN112BY(N) D	4.6 (ac)	3.46
	SSRN140BY(N) D	4.3 (ac)	2.96
トリプル同時	SSRN160BY(N) M	4.8 (ac)	3.26
床置形			
標準ペア	SSRV50BYV	5.4 (af)	4.09
	SSRV50BYT	5.4 (af)	4.09
	SSRV56BYV	5.3 (af)	3.93
	SSRV56BYT	5.3 (af)	3.93
	SSRV63BYV	5.3 (af)	3.84
	SSRV63BYT	5.3 (af)	3.84
	SSRV80BYV	5.0 (af)	3.50
	SSRV80BYT	5.0 (af)	3.50
	SSRV112BY	5.4 (ag)	3.89
	SSRV140BY	5.0 (ag)	3.17
	SSRV160BY	4.8 (ag)	3.08
ツイン同時	SSRV112BYD	5.5 (ag)	3.93
	SSRV140BYD	5.1 (ag)	3.42
	SSRV160BYD	5.0 (ag)	3.07
トリプル同時	SSRV160BYM	5.0 (ag)	3.46
厨房用エアコン			
標準ペア	SSRT80BYV	4.4 (af)	3.02
	SSRT80BYT	4.4 (af)	3.02
	SSRT140BY	4.5 (ag)	2.83
ツイン同時	SSRT160BYD	4.3 (ag)	2.83